#### Bowers & Wilkins

# 600 Series Anniversary Edition



# For the love of music.

For decades, we have poured our passion for performance and our love of music into everything we do, from our most affordable loudspeakers to our studio-quality 800 Series Diamond range. Now, our 600 Series has turned 25 – an occasion we think is worth celebrating in style.

# 25 years of great sound

Since 1995, well over a million satisfied customers have had their first experience of Bowers & Wilkins sound thanks to a pair of 600 Series loudspeakers. Now, we're proud to release the seventh generation of our affordable and iconic best-selling range.





# Engineered for better sound

600 Series Anniversary Edition includes proven drive units derived from the 800 Series Diamond. It partners those superior ingredients with carefully upgraded crossover components, resulting in even better resolution and superlative musicality.

# Designed to look beautiful

We offer two new finishes to match that improved sound quality. Every buyer across the globe can now select 600 Series Anniversary Edition in a stunning Oak finish to match Matte White and Matte Black. We also offer a Red Cherry finish in Asia.



#### 603 S2 Anniversary Edition

Technical features Decoupled Double Dome aluminium tweeter Continuum cone FST™ midrange

Paper bass cone Flowport™

Description 3-way vented-box system

Drive units 1x ø25mm (1 in) aluminium dome high-frequency

-6dB at 29Hz and 33kHz

1x ø150mm (6 in) Continuum cone FST midrange 2x ø165mm (6.5 in) Paper bass cone

Frequency Response 48Hz - 28kHz ±3dB Sensitivity 88.5dB spl (2.83V, 1m)

Harmonic Distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 90Hz - 22kHz <0.5% 120Hz - 20kHz 80 (minimum 3 00)

Recommended amplifier power

Nominal impedance

Frequency Range

30W - 200W into  $8\Omega$  on unclipped programme

Dimensions

985mm (38.8 in) cabinet only 1055mm (41.5 in) with plinth

Width:

190mm (7.5 in) cabinet only 320mm (12.6 in) with plinth

Depth:

340mm (13.4 in)

370mm (14.6 in) with plinth

24.1kg (53.1 lb) Net Weight

**Boxed Weight** 31.7kg (69.9 lb - single)

Cabinet: Grille: Finishes

> Matte Black Black Matte White Grey Oak Grey Red Cherry Black



## 606 S2 Anniversary Edition

Technical features Decoupled Double Dome aluminium tweeter Continuum cone bass / midrange

Flowport™

Description 2-way vented-box system

1x ø25mm (1 in) aluminium dome high-frequency 1x ø165mm (6.5 in) Continuum cone bass / midrange Drive units

Frequency Range -6dB at 40Hz and 33kHz Frequency Response 52Hz - 28kHz +3dB

Sensitivity 88dB spl (2.83Vrms, 1m)

**Harmonic Distortion** 2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz

<0.5% 150Hz - 20kHz

Nominal impedance 8Q (minimum 3.7Q)

Recommended amplifier power 30W - 120W into  $8\Omega$  on unclipped programme

Dimensions Height:

345mm (13.5 in) Width:

190mm (7.5 in)

Depth:

300mm (11.8 in) cabinet only 324mm (12.8 in) including grille

and terminals

6.9kg (15.2 lb) **Net Weight** 16kg (35.3 lb - pair) **Boxed Weight** 

Finishes Cabinet: Grille:

> Matte Black Black Matte White Grev Grey Red Cherry Black



### 607 S2 Anniversary Edition

Technical features Decoupled Double Dome aluminium tweeter

Continuum cone bass / midrange Flowport™

Description 2-way vented-box system

Drive units 1x ø25mm (1 in) aluminium dome high-frequency 1x ø130mm (5 in) Continuum cone bass / midrange

-6dB at 40Hz and 33kHz

52Hz - 28kHz ±3dB Frequency Response Sensitivity 84dB spl (2.83V, 1m)

Harmonic Distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 110Hz - 22kHz <0.5% 180Hz - 20kHz

Nominal impedance

Recommended amplifier power

Frequency Range

30W - 100W into  $8\Omega$  on unclipped programme

Dimensions

300mm (11.8 in) Width: 165mm (6.5 in)

207mm (8.1 in) cabinet only 231mm (9.1 in) including grille and terminals

Net Weight 4.7kg (10.4 lb) **Boxed Weight** 11.2kg (24.7 lb - pair)

Finishes Cabinet:

Matte Black Black Matte White Grey Grev Red Cherry



## HTM6 S2 Anniversary Edition

Technical features Decoupled Double Dome aluminium tweeter

Continuum cone bass / midrange Flowport™

Description 2-way vented-box system

Drive units 1x ø25mm (1 in) aluminium dome high-frequency

2x ø130mm (5 in) Continuum cone bass / midrange

Frequency Range -6dB at 42Hz and 33kHz 72Hz - 28kHz ±3dB Frequency Response Sensitivity 87dB spl (2.83Vrms, 1m)

Harmonic Distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 100Hz - 22kHz <0.5% 200Hz - 22kHz

Nominal impedance

Recommended amplifier power 30W - 120W into  $8\Omega$  on unclipped programme

Dimensions Height:

160mm (6.3 in) Width: 480mm (18.9 in)

255mm (10.0 in) cabinet only 279mm (11.0 in) including grille and terminals

Net Weight 7.8kg (17.2 lb) **Boxed Weight** 9.2kg (20.3 lb - single)

Finishes Cabinet: Matte Black Black

Matte White Grey Oak Grev Red Cherry

